

TECHNICAL DATA SHEET

DIMENSIONS

Length	1218mm
Width	239mm
Thickness	8mm
Bevels	Square edge
Number of panels per pack	9
m2 per pack	2.62m2
Joining system	Uniclic 4 sides

PROUCT OVERVIEW



Wearing Layer: Imported Europe abrasion paper ,more than 6000 rpm.

Decorative Layer: Super clear wood grain,UV curing to keep lock the color.

Base Material Layer: Special customized environmental protection substrate,meticulous and soild.

Balance Layer: Good moisture resistance to keep the floor stability.

GENERAL DATA

	METHODS	PARAMATERS
Wear resistance	EN 13329	>4,000 cycles
Wear class	EN 13329	AC4
Impact resistance	EN 13329	IC2
Scratch resistance	EN 438-2:25	Charge \geq 3N
Effect of a castor chair	ISO 4918	25,000 cycles
Thickness swelling	ISO 24336	\leq 18%
Locking strength	ISO 24334	F10.2 long side \geq 1 kN/m
		Fmax long side \geq 1 kN/m
		Fs0.2 short side \geq 2 kN/m
Effect of furniture leg	EN 424	Fmax short side \geq 2 kN/m
		No visible Damage
Surface soundness	EN 13329	\geq 1.25N/mm2
Static indentation	EN 24343	\leq 0.05mm
Light fastness	EN ISO 105 B02	Class > 6
Dimensional tolerances of the board according to ISO 24337	ISO 24337	length \pm 0,5 mm
		width \pm 0,1 mm
		thickness \pm 0,5 mm